

TABLE OF 'X' DIMENSIONS **ICOMMERCIAL OR** RESIDENTIAL)

CURB FACE	"x"
LESS THAN 6"	2.5'
6" to 7"	3'
over 7" to 8"	3.5'
over 8" to 9"	4'
over 9" to 10"	4.5'
over 10" to 11"	5'
over 11" to 12"	5.5'
over 12" to 13"	6'
over 13"	6.5'

ELEVATION

NOTES:

- ALL WORK SHALL BE DONE IN ACCORDANCE WITH "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION," LATEST EDITION.
- 2. "W", ON COMMERCIAL DRIVEWAYS SHALL BE A MINIMUM OF 3.7 m (12') AND A MAXIMUM OF 7.9 m (26') (EXCEPT IN SPECIAL CASES).
- 3. "W", ON RESIDENTIAL DRIVEWAYS SHALL BE A MINIMUM OF 3.7 m (12') AND A MAXIMUM OF 5.5 m (18') (EXCEPT IN SPECIAL CASES).
- 4. MINIMUM DISTANCE BETWEEN DRIVEWAYS (TOP "X" TO TOP "X") SHALL BE 0.6m (2') OF FULL HEIGHT CURB.
- 5. "Y" IS GENERALLY EQUAL TO "P" BUT SHALL NOT BE GREATER THAN "A" "B" NOR LESS THAN "X".
- 6. WHERE "P" IS GREATER THAN "X"," Y" SHALL NOT LESS THAN "P".
- 7. RESIDENTIAL DRIVEWAYS WHERE "P" IS LESS THAN 1.2 m (4') SHALL BE CONSTRUCTED AS COMMERCIAL DRIVEWAYS.
- 8. JOINTS, SCORING AND CONCRETE SPECIFICATIONS PER STD. PLAN S-421

CITY OF PASADENA - DEPARTMENT OF PUBLIC WORKS DRAWN BY: REVISION: UNITS: MARCOS TIEMANN DUAL DRIVEWAY-DUSTPAN TYPE STANDARD PLAN: CHECKED BY: ROWENA HINGCO APPROVED BY: SUBMITTED BY **GIL WEISS** RCE NO. 38689 EXPIRES MARCH 31, 2007